





- High stability rating
- Ease of maintenance
- Reusable
- Individual modules
- Compatible with all types of wall
- No visible fixings
- Fire classified

DEKO BK is a specially developed aluminium framework which is compatible with DEKO system partitions, glazed partitions, and other types of concrete wall, brick wall, and drywall.

Fire rated glass is installed with special glass beads without the need for visible screws.

DEKO BK can be constructed to form continuous glazed partitions or can be installed as individual glazed modules. The modules are either single or double glazed.

For further information and reference photos please visit www.dekobk.com.



## Type Summary - DEKO BK

Туре	Partition Thickness (mm)	Glazed Module (Number)	Glass thickness	Weight (kg/sqm)	Airborne Sound Insulation (Rw)	Fire Resistance
BK EW30	92-230	1/2	7 mm fire rated glass	20/35	32 (37) dB*	E30/EW30
BK EI30	92-230	1/2	12 mm fire rated glass	30 / 45	37 (39) dB*	EI30
BK EW60	92-230	1/2	15 mm fire rated glass	40 / 55	38 (41) dB*	EW60
BK El60	92-230	1/2	24 mm fire rated glass	60 / 75	39 (42) dB*	EI60

<sup>\*)</sup> The value in brackets states the sound reduction with an extra layer of 6 mm double glazing.

