





- Individual modules
- Several module joint options
- Extensive range of doors in different heights
- Specially developed aluminium frame system for doors
- Various widths and types of glass available
- Film manifestations to any design available
- Ease of maintenance
- Sound tested
- Fire tested
- Demountable and reusable

DEKO fully glazed partitions are characterised by simplicity, ensuring maximum light and natural, open working environments.

DEKO FG is based on single glazed modules built from floor to ceiling with slim aluminium sections which compliment joints with other building components.

For further information and reference photos please visit www.dekofg.com.



Type Summary - DEKO FG

Туре	Partition Thickness (mm)	Glazed Module (Number)	Glazing Sizes (mm)	Weight (kg/sqm)	Airborne Sound Insulation (Rw)	Fire Resistance
DEKO FG	27-30	1	10, 12, 15	25, 30, 38	35-36 dB*	Unclassified**
FG Fire EW30	35	1	18	45	40 dB	EW30
FG Fire El30	39	1	23	58	42 dB	EI30
FG Fire EW60	39	1	23	58	42 dB	EW60
FG Fire El60	44	1	28	70	43 dB	El60

^{*)} Officially tested at DELTA with 12 mm glass and tight profile or sealed joint. Sound absorption can be improved additionally by using laminated high acoustic glass.



^{**)} The DEKO FG partition with dedicated sprinkler system fulfils EI60 fire requirements.